



INVERTER BATTERY

DIFFERENT CONCEPT- LATEST TECHNOLOGY

Your own **Husky Battery** high performance brand introduces better than ever range of products with a commitment of even better durability, low maintenance and high power backups. 5M Product is already exported to various countries.

5M batteries are manufactured under the aegis of Industry Experts, renowned scientists and researchers. Our experts warrant corrosion resistant and low maintenance batteries with the help of a unique combination of Lead-Calcium-Antimony-Selenium-Tin alloy. The end user gets a robust product with the help of pressure die casting technology incorporated. We use internationally researched curing and aging processes to get required porosity, mechanical strength, cohesion, adhesion, and electrical performance. High standards of carbon used reduces sulphation and increase life of battery by at least three times. Battery is capable of recovering from deep discharge because of high capacity and charge acceptance. Before delivery the product in-house laboratory testing and Optical emission spectro photometry is done. Our company is ISO certified and the product complies with BIS standards.

BATTERY SPECIFICATIONS

BATTERY MODEL	Free Replacement Warranty Months #	Nominal Voltage (V)	Reserve Capacity @ C/20 (AH)	Backup at 400W (33AMPS) H:MM	Filled Weight (Kg) +/- 5%	Battery Type *
TT 2024 TT2030	24 & 30	12	150	3:00	56.0	6.2/260/5
TT 2124 TT2130	24 & 30	12	165	3:30	57.0	6.2/180/7
TT 2224 TT2230	24 & 30	12	180	4:00	59.0	6.2/200/7
TT 2324 TT2330	24 & 30	12	200	4:30	63.0	6.2/220/7
TT 2424 TT2430	24 & 30	12	220	4:45	63.0	6.2/240/7
TT 2524 TT2530	24 & 30	12	240	5:00	65.0	6.2/260/7

PER CELL SPECIFICATIONS :

* Per Cell Specifications | Filling in Gravity of Electrolyte at 27 Degree Centigrade | Specific Gravity of Electrolyte in fully charged condition - 1.240 (+/- 0.010 points) | Top Charge Voltage will be around 16.0V-16.5V | Cut-off voltage 1.75Volts / Cell at C/20 Capacity | Automotive Batteries are Standard Flat Plates | Capacity C/20: Fully charged batteries are discharged at constant current for total of 20 hrs, till voltage of battery falls down to 10.5 volt | Back up@400 w: fully charged batteries are discharged at const current of 33 amps, till the voltage falls down to 10.5 volt | # Refer Warranty Card

5M

PROWESS



AMERICAN
STANDARD

INVERTER BATTERY
DIFFERENT CONCEPT- LATEST TECHNOLOGY

NEXT GENERATION

ELECTRO-ENERGETIC

SUPER PERFORMANCE

product by :
HUSKY
Different Concept - Latest Technology

